

ELECTRICAL PARAMETERS

Performance at STC (Power Tolerance 0 ~ +3%)

Maximum Power (Pmax/W)	440	445	450	455	460
Operating Voltage (Vmpp/V)	41.6	41.8	42.0	42.2	42.4
Operating Current (Impp/A)	10.58	10.65	10.72	10.79	10.86
Open-Circuit Voltage (Voc/V)	50.0	50.2	50.4	50.6	50.8
Short-Circuit Current (Isc/A)	11.22	11.29	11.36	11.43	11.50
Module Efficiency ηm(%)	20.2	20.5	20.7	20.9	21.2

Performance at NMOT

Maximum Power (Pmax/W)	327	330	334	337	341
Operating Voltage (Vmpp/V)	38.9	39.1	39.3	39.4	39.6
Operating Current (Impp/A)	8.41	8.47	8.52	8.57	8.62
Open-Circuit Voltage (Voc/V)	46.8	46.9	47.1	47.3	47.5
Short-Circuit Current (Isc/A)	9.04	9.10	9.16	9.21	9.27

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5 NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Air Mass AM1.5, Wind Speed 1m/s

Electrical characteristics with different rear side power gain (refer to 440W front)

Pmax gain	Pmax/W	Vmpp/V	Impp/A	Voc/V	Isc/A
5%	462	41.6	11.11	50.0	11.78
10%	484	41.6	11.64	50.0	12.34
15%	506	41.6	12.17	50.0	12.90
20%	528	41.6	12.70	50.2	13.46
25%	550	41.6	13.23	50.2	14.03

MECHANICAL SPECIFICATION

Cell Type	Monocrystalline
Cell Dimensions	166*166mm
Cell Arrangement	144 (6*24)
Weight	28kg (61.73lbs)
Module Dimensions	2094*1038*30mm (82.44*40.87*1.18inches)
Cable Length (Portrait)	Portrait 300mm/Landscape 1200mm/Customized
Cable Cross Section Size	TUV: 4mm ² (0.006inches ²)/UL: 12AWG
Front Glass	2.0mm (0.08 inches) AR Coating Semi-tempered Glass
Back Glass	2.0mm (0.08 inches) Glazed Semi-tempered Glass
No. of Bypass Diodes	3/6
Packing Configuration (1)	35pcs/carton, 770pcs/40hq
Packing Configuration (for USA)	36pcs/carton, 648pcs/40hq
Frame	Anodized Aluminium Alloy
Junction Box	IP68


OPERATING CONDITIONS

Maximum System Voltage	1500V/DC(IEC)
Operating Temperature	-40°C ~ +85°C
Maximum Series Fuse	25A
Static Loading	Snow Loading: 5400Pa/ Wind Loading: 2400Pa
Conductivity at Ground	≤0.1Ω
Safety Class	II
Resistance	≥100MΩ
Connector	T01/LJQ-3-CSY/MC4/MC4-EVO2
Backside Output Ratio*	70% ± 5%
*Under STC: Backside Output Ratio = $P_{\max(\text{rear})} / P_{\max(\text{front})}$	


TEMPERATURE COEFFICIENT

Temperature Coefficient Pmax	-0.36%/°C
Temperature Coefficient Voc	-0.26%/°C
Temperature Coefficient Isc	+0.043%/°C
NMOT	43±2°C

I-V CURVE



TECHNICAL DRAWINGS



Konark Energy Inc

Add: 7433 Las colinas blvd ste 101, Irving, TX, 75063

Tel:+1-214-366-1070

E-mail:info@Konarkinc.com

www.Konarkinc.com

